


ExMP32N

Explosion Proof LED Right Angle Torch



Description

- Suitable for explosive environment class I, class II zone 0, 1, 2, class III zone 20, 21, 22 and other professional portable lighting.
- Intrinsically safe explosion-proof design.
- The body is made of permanent anti-static, anti-aging and anti-corrosion high-strength alloy plastic injection molding, compact and lightweight, easy to carry.
- Professional optical lens design, soft illumination, uniform spot, in line with GB 30734 fire protection standard.



Parameters

| | |
|------------------------|--|
| Certifications: | IECEX, ATEX |
| Ex mark: | IECEX: Ex ia I Ma; Ex ia IIC T4 Ga; Ex ia IIIB T130°C Da ATEX: I M1 Ex ia I Ma II 1 G D Ex ia IIC T4 Ga; Ex ia IIIB T130°C Da |
| Usage: | I, II Zone 0/1/2, and III Zone 20/21/22 |
| Working ambient temp.: | -40°C ≤ Ta ≤ +55°C |
| Ingress protection: | IP66/67 |
| Rated voltage: | 3×1.5V |
| Power: | 1.5W |
| CCT: | 6500K |
| Luminous flux: | ≥200lm (strong mode), ≥70lm (work mode) |
| Run time: | ≥8h (strong mode), ≥15h (work mode) |
| Battery type: | 3×LR6AA (IEC60086) |
| Lifespan: | 50,000h (without battery) |

Features



Order specifications

| Illustration | Luminous flux | Run time | Weight (g) | Order No. |
|--------------|---|---|------------|-----------|
| | Work mode: $\geq 70\text{lm}$ Strong mode: $\geq 200\text{lm}$ | Work mode: $\geq 15\text{h}$ Strong mode: $\geq 8\text{h}$ | 220 | ExMP32N |

Spare parts

| Illustration | Description | Weight (g) | Order No. |
|----------------------|-----------------|------------|-----------|
| Alkaline battery | 1.5V (IEC60086) | 24 | LR6AA |

Outline dimension (unit: mm)

